



The **Automatic FD 382 Document Folder** offers any business, church, school or print for pay center quick, easy set-up, and the versatility to complete a variety of fold jobs in minutes. Jobs are completed exceptionally fast with the FD 382, folding up to **20,100 pieces per hour!** Fully automated fold plates provide one touch setup of the 18 pre-programmed fold settings or for choosing one of the 25 custom folds that can be stored into memory. In addition, the new 2.8" (71mm) backlit LCD display and control panel makes the FD 382 extremely easy to use with a step by step user interface that is second to none.

Operators can load up to 500 sheets in the hopper, select their fold, press start and walk away to attend to other important tasks. The FD 382 will fold the 500 sheets in as fast as 2 minutes and hold the folded pieces on its patented **Telescoping Conveyor System**.

The patented **Multi-Sheet Feeder** is an optional feature that allows up to 4 sheets stapled or unstapled to be folded at one time through the dedicated feed system with its own side guides and skew adjustment system.

The large 2.8" (71mm) backlit LCD display and user friendly control panel allows for untrained operators to walk up and start folding with little to no instruction. The FD 382 advanced software allows for all standard fold types and paper sizes to be customized to meet your particular needs.

When it comes to paper folding, no one does it faster or with higher quality than the Formax FD 382!

Standard Fold Types



Letter



Zig Zag



Half



Gate



Fold Out



Double Parallel

Operating Features

Fast! Up To 20,100/Hour: Large jobs are processed quickly at speeds of up to 20,100 pieces per hour

Large LCD Interface: A large 2.8" (71mm) backlit LCD screen and user friendly controls allow anyone to walk up and start folding in seconds

Drop-In Feed System: Three-roller drop-in feed system produces dependable feeding of forms with no fanning required

Adjustable Stacker Wheels: Stacker wheels can be manually adjusted to neatly and sequentially stack different paper sizes and fold types

Telescoping Conveyor System: Conveyor can be set between 14" (356mm) and 36" (915mm) in length and holds up to 500 folded pieces

Noise Reduction: Fold plates are enclosed and insulated to reduce operating noise

6-Digit Resettable & 8-Digit Life Counters: Provides maximum audit control

AutoBatch™: Programmable to process pre-set number of sheets into sets with a delay

Folding Features

Six Standard Folds in Common Paper Sizes: Pre-programmed for 6 popular fold types in letter, legal and ledger paper sizes equalling 18 preset fold settings

Stores 25 Custom Folds: Up to 25 custom folds can be programmed and stored into memory

Optional Dedicated Multi-Sheet Feeder: Allows for up to 4 stapled or unstapled sheets to be folded at once, with the ability to select standard or custom folds in letter and legal paper sizes

Standard Fold Settings Modification: Even the six standard fold types can be modified individually for each paper size for maximum flexibility and customization

Cross-Folding: A guide is included for two pass operation

Technical Features

Easy-Off Feed Wheel Shaft: Feed wheels can be changed without removing side covers

Thick Stock Mode: Speed can be temporarily increased to help feed thicker stocks

Seven Point Fold Stops: Fold plates utilize seven point fold stops for crisp, accurate folds of large paper sizes at high speeds

Removable Roller Cover: Easily removed for improved access to fold rollers and exit area

Six Languages: Language selections include English, Spanish, French, German, Italian & Dutch

Specifications

Speed:	Up to 20,100 sheets per hour – based on 11" (279mm) Z-Fold*, 6 Settings
Hopper Capacity:	Up to 500 sheets 20# (75 gsm)
Pre-Set Folds:	Pre-programmed for C,V,Z, Gate, Fold Out and Double Parallel
Pre-Set Paper Sizes:	11", 14", 17", A5, A4, A3, B6, B5, B4
Custom Folds:	Stores up to 25 custom folds into memory
Paper Size:	Min: 3.5" W x 5" L (88.9 W x 127 L mm) Max: 12.25" W x 18" L (311 W x 457 L mm)
Languages:	English, Spanish, French, German, Italian & Dutch
Dimensions:	Closed: 33" L x 20" W x 19" H (84 L x 51 W x 48 H cm) Fully Extended: 60" L x 20" W x 19" H (152 L x 51 W x 48 H cm)
Weight:	73 lbs (33kg)
Power:	110-240VAC 50/60 Hz
Option:	FD 300-20 - Multi-Sheet Feeder
Safety Certifications:	UL & CE applied for


* Max speed based on Thick Stock Mode




Large LCD Interface



Optional Multi-Sheet Feeder



Closed Conveyor



Removable Feed Wheels

Formax - New Hampshire, USA
www.formax.com

Local Dealer: